

TREKKER4



TREKKER4 F-M

4-085 • 4-095 • 4-105 • 4-110 • 4-120

Landini

Passion for Innovation.

		TREKKER 4-085 F/M	TREKKER 4-095 F/M	TREKKER 4-105 F/M	TREKKER 4-110 F/M	TREKKER 4-120 F/M
ENGINE						
Manufacturer		Deutz AG				
Model		TCD 2.9 L4 HT	TCD 2.9 L4 HP			
Max power (ISO)	hp/kW	75 / 56	90 / 66	95 / 70	102 / 75	112 / 82
Max torque	Nm	375	378	400	410	420
Displacement	cm³	2900				
Cylinders / Valves		4 TA / 8				
Emissions category		Stage V				
CAPACITIES						
Fuel tank	l	85				
TRANSMISSION						
Type		Speed Four				
No. of gears FWD+REV		● 16+8 Hi-Lo Overdrive - ○ 16+8 w/creeper				
Transmission control		Manually operated - 12" independent dry clutch				
Reverse shuttle		Mechanical synchro shuttle				
Transmission oil cooler		●				
REAR PTO						
Type		Servoassisted dry clutch				
Speeds	rpm	● 540 / 540 E ○ 540 / 1000				
Rotation - spline shaft type		Clockwise (viewed from tractor rear) - 1-3/8" PTO shaft with 6 splines				
STEERING AND BRAKING SYSTEM						
Steering system		Hydrostatic Hi-Drive				
Steering control		2 independent levers with combined action on 2 wet clutches and on brakes				
Braking system		Hydrostatic wet multidisc graphite brakes				
HYDRAULIC SYSTEM						
Circuit type - pump type		Open centre - twin pump				
Flow rate hitch & remotes + steering	l/min	42 + 28				
Max operating pressure	bar	180				
Rear remote valves		● 3 ○ 4 / 5				
Front quick couplings		○ 6				
REAR HYDRAULIC HITCH						
Type		Mechanical with position/draft/mixed/float control				
Category - coupler type		● Cat.2 - fixed ball ends				
Max lift capacity at hitch points	kg	● 3150 ○ 4500 (w/assistor rams)				
DRIVING POSITION						
Cab type		○ 6-post high-visibility monocoque cab with opening rear window				
Cab suspension		suspended on hydro-silentblocks				
Cab air filter - filtration category		● dust filter - Cat.2 - ○ active carbon filter - Cat.4				
Air conditioning		● manual A/C				
Radio system		● radio ready - ○ DAB radio and sound system				
Platform type		ROPS w/central tunnel w/side gears and reverse shuttle controls				
Platform suspension		Suspended on hydro-silentblocks				
Lights		● Halogen driving and working lights - ○ LED driving and working lights				
Beacon light		●				
ON-BOARD TECHNOLOGY						
Digital dashboard		●				
WEIGHTS AND DIMENSIONS						
Wheelbase	mm	1650				
Ground clearance	mm	340				
Height over ROPS	mm	2400				
Max length without front weights	mm	3380				
Max overall width	mm	1410-1492 (metal F) - 1532 (rubber F) / 1700-1750 (M)				
Shipping weight	kg	3900 (F) / - 4500 (M)				
Front weight support		Built-in				
Front weights	kg	○ 6x30 / 8x30 / 8x30 + 33kg central front ballast				
TRACKS						
Bottom rollers		5				
Top carrier roller		Permanently lubricated				
Track tension adjustment system		Hydraulic track adjuster with permanently lubricated sprocket gear				
Front suspension		Leaf spring				
Rear suspension		Crossbar on independent track frames				
Track shoe type		● Metal ○ Rubber				
Track shoe width	mm	310-360 (metal F) / 400-450 (metal M) / 400 (rubber F/M)				

Key: ● standard ○ option

All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.