

# X5 HC



X5.100 HC - X5.110 HC



**McCORMICK**  
Power Technology.



ENGLISH

		X5.100 HC	X5.110 HC
<b>ENGINE</b>			
Rated power (97/68/EC - ISO TR 14396)	hp/kW	95/70	102/75
Max power (97/68/EC - ISO TR 14396)	hp/kW	95/70	102/75
Rated engine speed	rpm	2200	
Engine speed at max power	rpm	1900	
Max torque at 1400 rpm	Nm	395	430
Manufacturer		FPT	
Stage V / Tier 4 Final exhaust after-treatment system		DOC + SCRof	
Cylinders / Displacement / Valves		4 / 3.61 / 16V	
Engine Memo Switch		●	
<b>CAPACITIES</b>			
Fuel tank	l	135	
<b>TRANSMISSION</b>			
No. of gears - std		● 12 FWD + 12 REV with synchro shuttle - ○ 12 FWD + 12 REV with RPS with modulation control	
No. of gears - option 2		○ 24 FWD + 24 REV with Hi-Lo powershift - ○ 24 FWD + 24 REV with Hi-Lo powershift & RPS with modulation control	
Creeper		~	
Minimum speed with creeper	km/h	0.32 with 12+12 / 0.26 with Hi-Lo (IR 800mm)	
<b>REAR PTO</b>			
Type		● mechanical - ○ electrohydraulic	
Speeds	rpm	● 540 - ○ 540 / 540E - ○ 540 / 1000	
Ground speed PTO		○	
<b>FRONT AND REAR AXLES</b>			
Front rigid axle		●	
Traction type		● 4WD	
Front differential lock		Hydralock full locking differential	
Rear differential lock		● electrohydraulic	
<b>BRAKING SYSTEM</b>			
Front brakes		~	
Rear brakes		ring piston hydraulic brakes	
Trailer braking system		● dual-line hydraulic brake as per MR - ○ single-line hydraulic brake or CUNA	
<b>HYDRAULIC SYSTEM</b>			
Hydraulic pump for hitch & remote valves + steering - flow rate		● 62 + 32 l/min	
Rear remote valves - type, min - max		mechanical, 2 - 3	
Free-flow return		●	
<b>REAR 3-POINT HITCH</b>			
Rear hitch control		● mechanical - ○ mechanical with ELS	
Category - coupler type		II - ● fixed ball ends - ○ quick-hitch hooks - ○ telescopic lower links	
Max lifting capacity at hitch points	kg	● 3900 with twin assistor rams	
<b>CAB</b>			
In-cab noise level		78	
Work lights		● 4 work lights - 2 on roof front, 2 on roof rear - ○ 8 work lights - 2 on roof front, 2 on roof rear, 2 on bonnet, 2 on handles (LED)	
<b>ON-BOARD TECHNOLOGY</b>			
Rear ISOBus connection		○	
PSM Precision Steering Management and rear ISOBus - ready		●	
Fleet & Remote Diagnostics Management and McCormick Farm Pro Pack - 1 year		● - on selected markets	
<b>WEIGHTS AND DIMENSIONS</b>			
Max length with front weights - Width (min - max)	mm	4400 - (1782-2542) - measured with tyres 9.5R48 4WD	
Shipping weight - measured with average specs	mm	4300	

Key: ● standard ○ option ~ not available

All data and illustrations provided in this brochure are for information purposes only and can be changed.



via G. Matteotti, 7 | 42042 Fabbrico [RE] Italia  
 t. +39.0522.656.111 | f. +39.0522.656.476  
 webmaster@argotractors.com | www.argotractors.com



6737443A1 - 10/2023  
 graphic design: gruppo saldatori  
 bzzbzz@grupposalidatori.com

EN